



IP42 **IK05**

Downlight Ultra Compact LED

Installazione a incasso

W	• Dim (mm) • Ø H		Foro Ø
8	85	65	70

Downlight Ultra Compact LED										elplast [®] BEGHELLI	
W	Cod Ordine	Codice EAN	Assorbimento W	Temp. colore	Resa Cromatica	Flusso LED (lm)	Flusso (lm)	Efficienza Luminosa (lm/W)	Imb. singolo/multi		
8	71050	8002219722690	8	3000K	>80	1080	720	90	1/12		
8	71051	8002219722706	8	4000K	>80	1080	720	90	1/12		



IP40

RegLED Eco

Reglette

W	• Dimensioni (mm) • L B H		
4	313	22	30
8	573	22	30
10	873	22	30
14	1173	22	30
18	1473	22	30

RegLED Eco										CON INTERRUOTORE		elplast [®] BEGHELLI	
W	Cod Ordine	Codice EAN	Assorbimento W	Temp. colore	Resa Cromatica	Flusso LED (lm)	Flusso (lm)	Efficienza Luminosa (lm/W)	Imb. singolo/multi				
4	74040	8002219713339	4	3000K	>80	350	300	75	1/10				
8	74042	8002219713353	8	3000K	>80	700	600	75	1/10				
10	74044	8002219713377	9,5	3000K	>80	880	750	79	1/10				
14	74046	8002219713391	13,5	3000K	>80	1240	1050	78	1/10				
18	74048	8002219713421	16,5	3000K	>80	1600	1350	82	1/10				
4	74041	8002219713346	4	4000K	>80	380	320	80	1/10				
8	74043	8002219713360	8	4000K	>80	750	640	80	1/10				
10	74045	8002219713384	9,5	4000K	>80	950	800	84	1/10				
14	74047	8002219713414	13,5	4000K	>80	1320	1120	83	1/10				
18	74049	8002219713438	16,5	4000K	>80	1700	1440	87	1/10				



IP40

RegLED CCT

Reglette

3 TEMPERATURE COLORE SELEZIONABILI

W	• Dimensioni (mm) • L B H		
4	313	22	30
8	573	22	30
10	873	22	30
14	1173	22	30
18	1473	22	30

RegLED CCT										CON INTERRUOTORE		elplast [®] BEGHELLI	
W	Cod Ordine	Codice EAN	Assorbimento W	Temp. colore	Resa Cromatica	Flusso LED (lm)	Flusso (lm)	Efficienza Luminosa (lm/W)	Imb. singolo/multi				
4	74075	8002219743855	4	3000/4000/5000K	>80	400	340	85	1/10				
8	74076	8002219743862	8	3000/4000/5000K	>80	750	680	85	1/10				
10	74077	8002219743879	9,5	3000/4000/5000K	>80	950	850	90	1/10				
14	74078	8002219743886	13,5	3000/4000/5000K	>80	1320	1190	88	1/10				
18	74079	8002219743893	16,5	3000/4000/5000K	>80	1740	1530	93	1/10				