



FILETTO CON PASSO METRICO - EN 60423 - METRIC THREAD

Articolo Type	Filetto Thread	Conduttori Ø mm Clamping range cable Ø mm	Chiave D nut	Chiave E nut	L	Conf. pezzi Packing pcs.
BM 2812	M 12 x 1,5	4 - 6	13	14	5	100
BM 2816	M 16 x 1,5	8 - 10	15	17	6	100
BM 2820	M 20 x 1,5	10 - 12	20	22	7	50
BM 2825	M 25 x 1,5	17 - 19	28	30	8,5	50
BM 2832	M 32 x 1,5	19 - 22	33	35	9	50
BM 2840	M 40 x 1,5	26 - 30	42	45	10,2	25
BM 2850	M 50 x 1,5	39 - 41	54	57	10	10
BM 2863	M 63 x 1,5	43 - 45	60	64	12	10

Temperatura d'esercizio: -20°C +70°C
 per brevi periodi: +120°C

Range of temperature: -20°C +70°C
 for short time: +120°C

FILETTO PASSO PG - DIN 40430 - PG THREAD

Articolo Type	Filetto Thread	Conduttori Ø mm Clamping range cable Ø mm	Chiave D nut	Chiave E nut	L	Conf. pezzi Packing pcs.
BM 2596	PG 7	4 - 6	13	14	5	100
BM 2597	PG 9	8 - 10	15	17	6	100
BM 2598	PG 11	8 - 10	18	20	6	100
BM 2599	PG 13,5	10 - 12	20	22	6,5	50
BM 2600	PG 16	12 - 14	22	24	6,5	50
BM 2601	PG 21	17 - 19	28	30	7	50
BM 2602	PG 29	26 - 28	37	40	8	50
BM 2603	PG 36	33 - 35	47	50	9	20
BM 2604	PG 42	39 - 41	54	57	10	5
BM 2605	PG 48	43 - 45	60	64	10	5

FILETTO PASSO GAS - ISO 228/1 - GAS THREAD

Articolo Type	Filetto Thread	Conduttori Ø mm Clamping range cable Ø mm	Chiave D nut	Chiave E nut	L	Conf. pezzi Packing pcs.
BM 2450	1/4"	4 - 6	13	14	5	100
BM 2451	3/8"	8 - 10	15	17	6	100
BM 2452	1/2"	10 - 12	20	22	7	100
BM 2453	5/8"	12 - 14	22	24	7,5	100
BM 2454	3/4"	17 - 19	28	30	8,5	100
BM 2455	1"	19 - 22	33	35	9	50
BM 2456	1 1/8"	26 - 28	37	40	10,5	50
BM 2457	1 1/4"	26 - 30	42	45	10,2	25
BM 2458	1 1/2"	33 - 35	47	50	12	20
BM 2459	2"	43 - 45	60	64	12	20
BM 24592	2 1/2"	55 - 57	80	80	12	10
BM 24593	3"	67 - 69	95	95	20	10