

Prese mobili diritte
a cablaggio rapido
50-60Hz IP44

Corrente nominale (A)	Tensione nominale	Colore tensione	Poli	Rif. orario	Codice Palazzoli	Conf. N. pz.
16	110V	●	2P+⊕	4	720124	5
	110V	●	3P+⊕	4	720134	5
	110V	●	3P+N+⊕	4	720144	5
	230V	●	2P+⊕	6	720126	10
	230V	●	3P+⊕	9	720139	5
	230V	●	3P+N+⊕	9	720149	5
	400V	●	2P+⊕	9	720129	5
	400V	●	3P+⊕	6	720136	10
	400V	●	3P+N+⊕	6	720146	5
32	110V	●	2P+⊕	4	720224	5
	110V	●	3P+⊕	4	720234	5
	110V	●	3P+N+⊕	4	720244	5
	230V	●	2P+⊕	6	720226	5
	230V	●	3P+⊕	9	720239	5
	230V	●	3P+N+⊕	9	720249	5
	400V	●	2P+⊕	9	720229	5
	400V	●	3P+⊕	6	720236	5
	400V	●	3P+N+⊕	6	720246	5

Caratteristiche: tutti i prodotti sono confezionati singolarmente.

Prese mobili diritte
a cablaggio rapido
per applicazioni speciali
IP44

Corrente nominale (A)	Frequenza	Tensione nominale	Colore tensione	Poli	Rif. orario	Codice Palazzoli	Conf. N. pz.	
16	50-60Hz	500V	●	2P+⊕	7	720127	5	
	50-60Hz	500V	●	3P+⊕	7	720137	5	
	50-60Hz	500V	●	3P+N+⊕	7	720147	5	
	50-60Hz	600÷690V	●	3P+⊕	5	720135	5	
	50-60Hz	600÷690V	●	3P+N+⊕	5	720145	5	
	50-60Hz	>50V *	●	2P+⊕	12	721122	5	
	50-60Hz	>50V *	●	3P+⊕	12	721132	5	
	100-300Hz	>50V	●	2P+⊕	10	720120	5	
	100-300Hz	>50V	●	3P+⊕	10	720130	5	
	100-300Hz	>50V	●	3P+N+⊕	10	720140	5	
	>300-500Hz	>50V	●	2P+⊕	2	720122	5	
	>300-500Hz	>50V	●	3P+⊕	2	720132	5	
	>300-500Hz	>50V	●	3P+N+⊕	2	720142	5	
	60Hz	440÷460V	●	3P+⊕	11	720131	5	
	60Hz	440÷460V	●	3P+N+⊕	11	720141	5	
	CC	>50÷250V	●	2P+⊕	3	720123	5	
	CC	>250V	●	2P+⊕	8	720128	5	
	32	50-60Hz	500V	●	2P+⊕	7	720227	5
		50-60Hz	500V	●	3P+⊕	7	720237	5
		50-60Hz	500V	●	3P+N+⊕	7	720247	5
		50-60Hz	600÷690V	●	3P+⊕	5	720235	5
		50-60Hz	600÷690V	●	3P+N+⊕	5	720245	5
		50-60Hz	>50V *	●	2P+⊕	12	721222	5
		50-60Hz	>50V *	●	3P+⊕	12	721232	5
100-300Hz		>50V	●	2P+⊕	10	720220	5	
100-300Hz		>50V	●	3P+⊕	10	720230	5	
100-300Hz		>50V	●	3P+N+⊕	10	720240	5	
>300-500Hz		>50V	●	2P+⊕	2	720222	5	
>300-500Hz		>50V	●	3P+⊕	2	720232	5	
>300-500Hz		>50V	●	3P+N+⊕	2	720242	5	
60Hz		440÷460V	●	3P+⊕	11	720231	5	
60Hz		440÷460V	●	3P+N+⊕	11	720241	5	
CC		>50÷250V	●	2P+⊕	3	720223	5	
50/60Hz	380/440V	●	3P+⊕	3	720233	5		
50/60Hz	380/440V	●	3P+N+⊕	3	720243	5		
CC	>250V	●	2P+⊕	8	720228	5		

* Per trasformatore d'isolamento.

Caratteristiche: tutti i prodotti sono confezionati singolarmente.