

# Vertex S+

PRODUCT: TSM-NEG9R.28

DUAL GLASS MONOCRYSTALLINE MODULE

PRODUCT RANGE: 415-440W

440W

MAXIMUM POWER OUTPUT

0~+5W

POSITIVE POWER TOLERANCE

22.0%

MAXIMUM EFFICIENCY



### Small in size, bigger on power

- Up to 440W, 22.0% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping, lower series resistance, improved current collection and enhanced reliability
- Reduce installation cost with higher power bin and efficiency
- Boost performance in warm weather with low temperature coefficient and operating temperature



### Dual-glass Design, more secure and sustainable

- Upgraded dual glass of Vertex S, less prone to micro-cracks and scratches on the back during installation
- Double-glass + innovative non-destructive cutting for improved mechanical resistance and strength
- Excellent fire rating, weather resistance, salt spray, sand dust, ammonia performance which is fully applicable in coastal, high temperature, humidity area and harsh environment




### Ultra-low Degradation, longer warranty, higher output

- First-year degradation 1% and annual degradation at 0.4%
- Up to 25 years product warranty and 30 years power warranty




### Universal solution for residential and C&I rooftops

- Easy for integration, designed for compatibility with existing mainstream inverters and diverse mounting systems
- Perfect size and low weight for handling and installation
- Most valuable solution on low load capacity rooftops (weight similar to backsheet version)
- Mechanical performance up to 5400 Pa positive load and 4000 Pa negative load



### Trina Solar's Dual Glass Performance Warranty






### Comprehensive Products and System Certificates



ISO 9001: Quality Management System  
 ISO 14001: Environmental Management System  
 ISO14064: Greenhouse Gases Emissions Verification  
 ISO45001: Occupational Health and Safety Management System



## DIMENSIONS OF PV MODULE(mm)



## ELECTRICAL DATA (STC)

Peak Power Watts-P <sub>MAX</sub> (Wp)*	415	420	425	430	435	440
Power Tolerance-P <sub>MAX</sub> (W)	0 ~ +5					
Maximum Power Voltage-V <sub>MPP</sub> (V)	42.1	42.5	42.8	43.2	43.6	43.9
Maximum Power Current-I <sub>MPP</sub> (A)	9.85	9.89	9.92	9.95	9.99	10.02
Open Circuit Voltage-V <sub>OC</sub> (V)	50.1	50.5	50.9	51.4	51.8	52.2
Short Circuit Current-I <sub>SC</sub> (A)	10.50	10.54	10.57	10.60	10.65	10.68
Module Efficiency η <sub>m</sub> (%)	20.8	21.0	21.3	21.5	21.8	22.0

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5. \*Measuring tolerance: ±3%.

## ELECTRICAL DATA (NOCT)

Maximum Power-P <sub>MAX</sub> (Wp)	316	320	323	327	332	335
Maximum Power Voltage-V <sub>MPP</sub> (V)	39.3	39.6	39.9	40.3	40.6	40.9
Maximum Power Current-I <sub>MPP</sub> (A)	8.04	8.07	8.09	8.12	8.16	8.17
Open Circuit Voltage-V <sub>OC</sub> (V)	47.5	47.9	48.2	48.7	49.1	49.4
Short Circuit Current-I <sub>SC</sub> (A)	8.46	8.49	8.52	8.54	8.58	8.61

NOCT: Irradiance at 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s.

## MECHANICAL DATA

Solar Cells	Monocrystalline
No. of cells	144 cells
Module Dimensions	1762×1134×30mm (69.06×43.15×1.18 inches)
Weight	21.8kg (48.0lb)
Front Glass	1.6 mm (0.06 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	EVA/POE
Back Glass	1.6mm(0.06 inches), Heat Strengthened Glass
Frame	30mm (0.06 inches) Anodized Aluminium Alloy, Black
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ), Portrait: 350/280 mm(13.78/11.02 inches) Length can be customized
Connector	MC4 EVO2 / TS4*

\*Please refer to regional datasheet for specified connector.

## TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P <sub>MAX</sub>	-0.30%/°C
Temperature Coefficient of V <sub>OC</sub>	-0.24%/°C
Temperature Coefficient of I <sub>SC</sub>	0.04%/°C

## MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC)
Max Series Fuse Rating	20A

## WARRANTY

25 year Product Workmanship Warranty  
30 year Power Warranty  
1% first year degradation  
0.4% Annual Power Attenuation

(Please refer to product warranty for details)

## PACKAGING CONFIGURATION

Modules per box: 36 pieces  
Modules per 40' container: 936 pieces