

UPS PowerValue 11T G2 1 kVA B



UPS PowerValue 11T G2 1 kVA B

General Information

Extended Product Type	UPS PowerValue 11T G2 1 kVA B
Product ID	4NWP100160R0001
EAN	7640169261886
Catalog Description	UPS PowerValue 11T G2 1 kVA B
Long Description	VFI online double conversion;900W;8.5min;RS232;USB;mini COM slot
Number of Batteries	4

Additional Information

Apparent Power Output	1000 V·A
Battery Chemical Composition	Lead-Acid
Battery Runtime	5 minute [unit of time]
Battery Type	Portable
Battery Weight	2.5 kg
CN8	85044000
Communication Interface	EV004045 EV001552
Communication Protocol and Connection	SNMP
Connection Type	IEC C14
Country of Origin	China (CN)
Customs Tariff Number	85044000
Data Sheet, Technical Information	4NWD003883
Declaration of Conformity - CE	4NWD003869
EAN	7640169261886
ETIM 6	EC000382 - UPS
ETIM 7	EC000382 - UPS
Efficiency	Overall 89.00 % Economy Mode (Eco-Mode) 97.50 %
Environmental Information	No declaration needed
Harmonic Distortion	5.00 %
Input Voltage (U_{in})	220 V 230 V 240 V
Input Voltage Type	EV000460
Instructions and Manuals	4NWD003883
Invoice Description	UPS PowerValue 11T G2 1 kVA B
Minimum Order Quantity	1 piece

Number of Outputs	C13 Connection 4
Number of Phases	Primary - 1 Secondary - 1
Object Classification Code	G
Options Provided	Auto shut down function Potential free switch contact Network-management
Output Voltage (U_{out})	208 V 220 V 230 V 240 V
Package Level 1 Depth / Length	436 mm
Package Level 1 EAN	7640169261886
Package Level 1 Gross Weight	10.3 kg
Package Level 1 Height	330 mm
Package Level 1 Units	1 piece
Package Level 1 Width	240 mm
Power Factor	0.9
Product Main Type	PowerValue 11T G2
Product Name	UPS
Product Net Depth / Length	356 mm
Product Net Height	228 mm
Product Net Weight	9.3 kg
Product Net Width	144 mm
Rated Frequency (f)	Primary 50 Hz Primary 60 Hz Secondary 50 Hz Secondary 60 Hz
Rated Output Power	900 W
RoHS Date	0318
RoHS Information	4NWD003869
RoHS Status	Following EU Directive 2011/65/EU
Selling Unit of Measure	piece
Uninterruptible Power Supply Form Factor	Tower
Uninterruptible Power Supply Topology	On-Line Double Conversion
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

UPS and Power Conditioning → UPS → Single-Phase UPS → PowerValue 11T G2



