



Foto illustrativa

SPECIFICHE

Descrizione	Tipo di prodotto	Presa interbloccata con porta fusibili
	Codice articolo	363R6
	Serie commerciale	SERIE 15

Dati Generali	Poli	N° 3P+E	Tipo di materiale	Termoplastico
	Corrente	A 63	Stabilità dimensionale	°C -25 /+70
	Voltaggio	V~ 380-415	Resistenza test filo incandescente	°C +650 / +850
	Grado di protezione	IP 55	Temperatura di esercizio	°C -25 + 55
	Resistenza all'impatto	IK 08	Peso	kg 2,00
	Resistenza di isolamento	MΩ >10	Portafusibili tipo	D02-E18
			Adatto per fusibili (NON INCLUSI)	36x15
	Behaviour with chemical and atmospheric agents			
	Saline Solution	Acids	Bases	Solvents
	Resistant	Concentrated Diluted	Concentrated Diluted	Hexane Benzol Acetone Alcohol
	Resistant	Limited Resistant Resistant	Resistant Resistant	Not resistant Not resistant Not resistant Limited Resistant
				Mineral Oil UV rays
				Limited Resistant Limited Resistant Limited Resistant

Standard	CEI EN 60309-1	CEI EN 60309-2	CEI EN 60309-4	2014/35/UE
----------	----------------	----------------	----------------	------------

Packaging	Descrizione		N/pezzi	Peso/kg
	Articolo		1	2,00
	Confezione		1	2,09
	Imballo		30	25,7

Dimensioni

Technical drawing showing three views of a 63 Amp plug with dimensions:

- Front view: Width 135, Height 346, Mounting hole diameter 6.5.
- Side view: Depth 173, Total height 416, Mounting hole diameter PG29.
- Top view: Width 92, Height 302.

	63 Amp		
P	3	4	5
A	135	135	135
B	346	346	346
C	173	173	173



Reg. A.E.E n° IT1710000010057

DATA

11/11/2024

RESPONSABILE TECNICO

Romano Rosi

Via Marabotto, 180 | 29010 | Castelnuovo Fogliani, PC | ITALY
Tel. +39 0523 947166 | Fax +39 0523 947480 | E-mail info@rosi.it