



Immagine illustrativa

SPECIFICHE

Descrizione	Tipo di prodotto		Spina mobile bassa tensione 50/60 Hz IP54							
	Codice articolo		1009213							
	Serie commerciale		SERIE 10 IEC 309 IP54							
Dati generali	Poli	N°	2P+E	Tipo di materiale		Termoplastico				
	Corrente	A	16	Tipo di terminale		Taglio-croce PH2				
	Voltaggio	V~	200-250	Diametro ingresso terminale		mm	3,7			
	Posizione contatto di terra	h	6	Capacità di serraggio del morsetto		mm	6,5 - 15			
	Grado di protezione	IP	54	Stabilità dimensionale		°C	-25 /+70			
	Resistenza agli urti	IK	08	Test del filo incandescente		°C	+650 / +850			
	Resistenza all'isolamento	MΩ	>10	Temperatura di esercizio		°C	-25 + 55			
				Peso		Kg	0,114			
		Behaviour with chemical and atmospheric agents								
Saline Solution	Acids		Bases		Solvents			Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone			Alcohol
	Resistant	Limited Resistant	Resistant	Limited Resistant	Resistant	Not resistant	Not resistant			Resistant

Standard	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE	
Packaging	Descrizioni		N/pezzi	Peso/kg
	Articolo		1	0,114
	Confezione innerbox		10	1,23
	Imballaggio			

Assemble

A technical drawing of a plug assembly. The drawing shows a side profile of the plug. Dimension A is the total length of the plug. Dimension B is the height of the main body. Dimension C is the length of the central part. Dimension ØK is the diameter of the central part.

P
A
B
C
ØK
Wire flexible (mm²)

16 Amp		
3	4	5
150	150	150
56	60	73
110	110	110
6-15	6-15	8-16
1-2,5		

32 Amp		
3	4	5
172	172	172
73	73	79
125	125	125
11,5-21	11,5-21	11,5-21
2,5-6		



Reg. A.E.E.n° IT17100000010057

CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

DATA	RESPONSABILE TECNICO
30/04/2021	Romano Rosi

Via Marabotto, 180 | 29010 | Castelnuovo Fogliani, PC | ITALY
Tel. +39 0523 947166 | Fax +39 0523 947480 | E-mail info@rosi.it