



Foto illustrativa

SPECIFICHE

Descrizione	Tipo di prodotto	Presa Mobile
	Codice articolo	1008223
	Serie commerciale	SERIE 11

Dati generali

Poli	N° 2P+E	Tipo di materiale	Termoplastico							
Corrente	A 16	Tipo di terminale	Vite PH2							
Voltaggio	V~ 380-415	Diametro ingresso terminale	mm 3,7							
Posizione contatto di terra	h 6	Capacità di serraggio del morsetto del cavo	mm 6,5 - 15							
Grado di protezione	IP 66/67	Stabilità dimensionale	°C -25 /+70							
Resistenza all'impatto	IK 08	Resistenza test filo incandescente	°C +650 / +850							
Resistenza di isolamento	MΩ >10	Temperatura di esercizio	°C -25 + 55							
		Peso	kg 0,175							
Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Limited Resistant	Resistant	Resistant	Not resistant	Not resistant	Resistant	Not resistant	Limited Resistant

Standard	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
----------	----------------	----------------	------------

Packaging	Descriptions	N/pezzi	Peso/kg
	Articolo	1	0,175
	Confezione	10	1,84
	Imballo	150	28,22

Dimensioni

Technical drawing of a mobile power plug. The drawing shows the side profile of the plug with four dimensions labeled: A (total length), B (height of the plug body), C (length of the cable entry section), and ØK (diameter of the cable entry). The plug has a rectangular body with a circular contact point on the left and a cable entry on the right. The cable entry is a cylindrical section with a flange at the end.

	16 Amp			32 Amp		
P	3	4	5	3	4	5
A	165	157	157	170	170	170
B	80	85	95	97	99	106
C	110	110	110	125	125	125
Ø K	6-15	6-15	6-15	11,5-21	11,5-21	11,5-21
Wire flexible (mm²)		1-2,5			2,5-6	



Reg. A.E.E n° IT 17100000010057

DATA

11/11/2024

RESPONSABILE TECNICO

Romano Rosi