



Immagine illustrativa

SPECIFICHE

Descrizione	Tipo di prodotto		Spina mobile bassa tensione 50/60 Hz IP54								
	Codice articolo		1009215								
	Serie commerciale		SERIE 10 IEC 309 IP54								
Dati generali	Poli	N°	3P+N+E	Tipo di materiale					Termoplastico		
	Corrente	A	16	Tipo di terminale					Vite PH2		
	Tensione	V~	200/346-240/415	Diametro ingress terminale			mm	3,7			
	Posizione contatto di terra	h	6	Capacità di serraggio del morsetto			mm	6,5 - 15			
	Grado di protezione	IP	54	Stabilità dimensionale			°C	-25 / +70			
	Resistenza agli urti	IK	08	Test del filo incandescente			°C	+650 / +850			
	Resistenza all'isolamento	MΩ	>10	Temperatura di esercizio			°C	-25 + 55			
				Peso			kg	0,16			
		Behaviour with chemical and atmospheric agents									
Saline Solution		Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Limited Resistant	Resistant	Resistant	Not resistant	Not resistant	Resistant	Not resistant	Limited Resistant	
											

Standard	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
----------	----------------	----------------	------------

Packaging	Descrizioni		N/pezzi	Peso/kg
	Articolo		1	0,16
	Pacco		8	1,37
	Imballaggio			

Dimensioni

Technical drawing of a three-phase plug. The drawing shows the side profile of the plug with the following dimensions labeled:

- A**: Total length of the plug.
- B**: Height of the main body.
- C**: Length of the main body.
- ØK**: Diameter of the pin.

	16 Amp			32 Amp		
P	3	4	5	3	4	5
A	150	150	150	172	172	172
B	56	60	73	73	73	79
C	110	110	110	125	125	125
ØK	6-15	6-15	8-16	11,5-21	11,5-21	11,5-21
Wire flexible (mm²)	1-2,5			2,5-6		