



Immagine illustrativa

SPECIFICHE

Descrizione	Tipo di prodotto	Presa mobile bassa tensione 50/60 Hz IP54
	Codice articolo	1009524
	Serie Commerciale	SERIE 11 IEC 309 IP54

Dati generali

Poli	N°	3P+E	Tipo di materiale	Termoplastico						
Corrente	A	32	Tipo di terminale	Vite PH2						
Voltaggio	V~	380-415	Diametro ingresso terminale millimetro	4,6						
Posizione contatto di terra	h	6	Capacità di serraggio del morsetto millimetro	11,5 - 20						
Grado di protezione	IP	54	Stabilità dimensionale °C	-25 /+70						
Resistenza agli urti	IK	08	Test del filo incandescente °C	+650 / +850						
Resistenza all'isolamento	MΩ	>10	Temperatura di esercizio °C	,-25 + 55						
			Peso Kg	0,273						
Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Limited Resistant	Resistant	Resistant	Not resistant	Not resistant	Resistant	Not resistant	Limited Resistant

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
-----------	----------------	----------------	------------

Packaging	Descrizioni		N/pezzi	Peso/kg
	Articolo		1	0,273
	Confezione		4	1,182
	Imballaggio		60	18,35

Dimensioni

Technical drawing of a circuit breaker showing dimensions A, B, C, and ØK. Dimension A is the total width, B is the height, C is the width of the main body, and ØK is the diameter of the terminal.

	16 Amp			32 Amp		
P	3	4	5	3	4	5
A	157	157	157	178	178	178
B	85	91	97	105	105	105
C	110	110	110	125	125	125
Ø K	6-15	6-15	8-16	11,5-21	11,5-21	11,5-21
Wire flexible (mm²)	1-2,5			2,5-6		



Reg. A.E.E n° IT17100000010057

CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

DATA	RESPONSABILE TECNICO
06/09/2024	Romano Rosi