



Immagine illustrativa

SPECIFIC

Descrizione	Tipo di prodotto	Spina mobile bassa tensione 50/60 Hz IP54
	Codice articolo	1009214
	Serie commerciale	SERIE 10 IEC 309 IP54

Dati generali

Poli	N°	3P+E	Tipo di materiale		Termoplastico					
Corrente	A	16	Tipo di terminale		Taglio-croce PH2					
Voltaggio	V~	380-415	Diametro ingresso terminale	mm	3,7					
Posizione contatto di terra	h	6	Capacità di serraggio del morsetto	mm	6,5 - 15					
Grado di protezione	IP	54	Stabilità dimensionale	°C	-25 /+70					
Resistenza agli urti	IK	08	Test del filo incandescente	°C	+650 / +850					
Resistenza all'isolamento	MΩ	>10	Temperatura di esercizio	°C	-25 + 55					
			Peso	Kg	0,142					
Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Limited Resistant	Resistant	Resistant	Not resistant	Not resistant	Resistant	Not resistant	Limited Resistant

Standard	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
----------	----------------	----------------	------------

Packaging	Descrizioni	N/pezzi	Peso/kg
	Articolo	1	0,142
	Confezione	10	1,51
	Imballaggio	150	23,27

Dimensioni

Technical drawing of a three-phase plug. The drawing shows the side profile of the plug with the following dimensions labeled: A (total length), B (height of the main body), C (length of the central locking mechanism), and ØK (diameter of the pin).

	16 Amp			32 Amp		
P	3	4	5	3	4	5
A	150	150	150	172	172	172
B	56	60	73	73	73	79
C	110	110	110	125	125	125
ØK	6-15	6-15	8-16	11,5-21	11,5-21	11,5-21
Wire flexible (mm²)		1-2,5			2,5-6	



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057

DATA	RESPONSABILE TECNICO
08/08/2024	Romano Rosi