



Immagine illustrativa

SPECIFICHE

Descrizione	Tipo di prodotto	Presa mobile bassa tensione 50/60 Hz IP54
	Codice articolo	1009224
	Serie commerciale	SERIE 11 IEC 309 IP54

Dati generali	Poli		N° 3P+E	Tipo di materiale		Termoplastico				
	Corrente		A 16	Tipo di terminale		Taglio-croce PH2				
	Tensione		V~ 380-415	Diamentro ingress terminale		mm	3,7			
	Posizione contatto di terra		h 6	Capacità di serraggio del orsetto		mm	6,5 - 15			
	Grado di protezione		IP 54	Stabilità dimensionale		°C	-25 / +70			
	Resistenza agli urti		IK 08	Test del filo incandescente		°C	+650 / +850			
	Resistenza all'isolamento		MΩ >10	Temperatura di esercizio		°C	-25 + 55			
				Peso		kg	0,179			
	Behaviour with chemical and atmospheric agents									
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Limited Resistant	Resistant	Resistant	Not resistant	Not resistant	Resistant	Not resistant	Limited Resistant

Standard	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
----------	----------------	----------------	------------

Packaging	Descrizioni		N/pezzi	Peso/kg
	Articolo		1	0,179
	Pacco		10	1,88
	Imballaggio		150	28,82

Dimensioni

Technical drawing of the cable head. Dimension A is the total length. Dimension B is the height of the main body. Dimension C is the length of the main body. Dimension ØK is the diameter of the flexible wire at the end.

	16 Amp			32 Amp		
P	3	4	5	3	4	5
A	157	157	157	178	178	178
B	85	91	97	105	105	105
C	110	110	110	125	125	125
Ø K	6-15	6-15	8-16	11,5-21	11,5-21	11,5-21
Wire flexible (mm ²)	1-2,5			2,5-6		



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Reg. A.F.E. n° IT17100000010057

DATA	RESPONSABILE TECNICO
08/08/2024	<i>Romano Risi</i>