



Illustrativo immagine

SPECIFICHE

Descrizione	Tipo di prodotto		Spina mobile								
	Codice articolo		1008213								
	Serie commerciale		SERIE 10								
Dati generali	Poli		N° 2P+E		Tipo di materiale				Termoplastico		
	Corrente		A 16		Tipo di terminale				Vite PH2		
	Voltaggio		V~ 200-250		Stabilità dimensionale				°C	-25 /+70	
	Posizione contatto di terra		h 6		Test del filo incandescente				°C	+650 / +850	
	Grado di protezione		IP 66/67		Temperatura di esercizio				°C	,-25 + 55	
	Resistenza agli urti		IK 08		Behaviour with chemical and atmospheric agents						
	Resistenza all'isolamento		MΩ >10								
	Behaviour with chemical and atmospheric agents										
	Saline Solution		Acids		Bases		Solvents				Mineral Oil
Concentrated			Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant		Limited Resistant	Resistant	Limited Resistant	Resistant	Resistant	Not resistant	Not resistant	Resistant	Not resistant	Limited Resistant
											
Standard	CEI EN 60309-1		CEI EN 60309-2		2014/35/UE						
Packaging			Descrizioni					N/pezzi		Peso/kg	
			Articolo					/		/	
			Confezione innerbox					/		/	
			Imballaggio					/		/	

Assemble

Technical drawing of a plug assembly. The drawing shows a side view of the plug with dimensions labeled: A (total length), B (height of the main body), C (length of the main body), and ØK (diameter of the pin). The plug has a rectangular main body with a central slot and a smaller rectangular section at the bottom. The pin is a standard two-pronged plug.

	16 Amp		
P	3	4	5
A	157	157	157
B	70	70	70
C	110	110	110
Ø K	6-15	6-15	8-16
Wire flexible (mm²)	1-2,5		



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015



Reg. A.E.E.n° IT17100000010057

DATA	RESPONSABILE TECNICO
30/04/2021	Romano Rosi

Via Marabotto, 180 | 29010 | Castelnuovo Fogliani, PC | ITALY
Tel. +39 0523 947166 | Fax +39 0523 947480 | E-mail info@rosi.it